



YÜKLEME TABLOSU LOADING TABLE

16 ton daraya göre
(According to 16 tonnes tare)

	A	B	C	D
S	48	56	64	74
120	00,0			

	Vagon Tipi Wagon Type	Sgmmns 40'
DARA Tare	KNORR Fren sistemi ile With the KNORR Brake System	≈16 000Kg
	WABTEC MZT Fren sistemi ile With the WABTEC MZT Brake System	≈16 000 Kg
BOJİ ÖZELLİKLERİ Bogie Features	Boji Tipi Bogie Type	Y25Lsd-KC1-K
	Dingil Yüğü Axle Load	22 500 Kg
	Ray Açıklığı Railway Clearance	1 435 mm
	Tekerlek Tipi ve Çapı Wheelset Type and Dia.	Monoblok / Ø920
	Dingil Eksenleri Arası Distance Between axes	1 800 mm
TAMPON Buffer	Tampon Buffer	According to UIC 526-1 Category A
	Tampon Tipi Buffer Type	with polymer pads, Max 116 Kg/pcs
	Tampon Siası Buffer Stroke	105 mm

CER Drawgear	Cer Tertibatı Tipi Drawgear Type	According to UIC 520/With the polymer pads / 1500 kN
	Çekme Kancası Coupler Hook	According to UIC 520 1500 kN
	Koşum Takımı Screw Coupler	According to UIC 520 1350 kN
FREN SİSTEMİ Brake System	Fren Tipi Brake Type	Compact Fren Sistemi Compact Brake System
	Sabo Tipi Brake Shoes Type	K Tipi Kompozit K Type Composite
	Eİ Fren Park Brake	Boji Üzerinde Integrated Bogie
	Boş Vagonun Max. Hızı Max. Speed of Empty Wagon	120 km/h
	Yüklü Vagonun Max. Hızı Max. Speed of Loaded Wagon	100 km/h
DiĞER ÖZELLİKLER Other Features	Kurp Yarıçapı Curve Radius	75 m
	Yükleme Yüksekliği Loading Height	1 155 mm
	Güvenlik Pimi Sayısı Number of ct. Spigots	12

YÜKLEME KAPASİTESİ LOADING CAPACITY

20', 30', 40' 45'
Konteynerler farklı
kombinasyonlarda

20', 30', 40' 45' Container.
Different Combinations



Sgmmns 40' Vagon Karakteristiği
Sgmmns 40' Wagon Characteristics

GR-110.00.00.00